

Maxidor CLASSIC Maxigate

Ideal APPLICATIONS for MAXIGATE

Normal front and back door where a D12 or V12 is not practical.

Outside quarters

Gate details

- 1) **Gate sizes:** 770mm x 1950mm
810mm x 1950mm
840mm x 1950mm
885mm x 1950mm
- 2) **Frame:** 25mm x 25mm square tubing
- 3) **Lock:** Double pin deadlock with 16 point star key
- 4) **Lock bar:** 25mm x 25mm square tubing (fixed to reveal)
- 5) Standard front and back door reveals from 780mm to 950mm width and 1970mm to 2100mm in height.
- 6) **Styled flights:** Steel flights (scissors type bracing connectors), join the uprights to each other. The "A" and "O" styles are unique to Maxidor (design Reg. No. 89/0267 & 89/0268). It is a refreshing move away from the conventional "X" style (still available from Maxidor) that make the doors more aesthetically pleasing.
- 7) **Lock Channel:** 25mm x 50mm square tubing
- 8) **Uprights:** 16mm square tubing



FEATURES:

- All **MAXIDOR™** components first go through a 5- stage phosphating, anti-corrosion treatment process.
- Welded in a pre-manufactured jig to ensure accurate specifications, consistent dimensions, no twisting or warping. Welding is done by CO2 to ensure complete bond and superior strength.
- Powder coated with polyester of a standard higher than normally required for similar applications. The T.G.I.C grade of powder used is the best available, conforms to European standards, is highly UV resistant and provides protection at least 30% (and up to 60%) better than the average powder coating.
- Fastened inside the reveal with security coach screws (break-off head screws), which are fixed into the reveal on each side at 3 equally spaced fixing points.